



EP303

Product name

Earth Positive® Zip-up Hoodie

Fibre composition / Yarn type

100% Organic Cotton Compact Spun

Fabric type / Weight

Brushed Fleece 3-ply 8.9 oz/yd² 300 g/m²

Commodity code

6110 2091 00

Origin

India

Available sizes

XS S M L XL 2XL 3XL

Certifications



Available colours



Size spec

Size	Width (A)		Length (B)	
	cm	inch	cm	inch
XS	53	20¾	66	26
S	56	22	69	27¼
M	59	23¼	72	28½
L	62	24½	75	29½
XL	65	25½	77	30¼
2XL	68	26¾	79	31
3XL	71	28	81	32

Discharge printing suitability

Important: This guide serves as a general reference, and results may vary. We strongly recommend testing prior to production.

Core colours

	Very Good	Moderate	Not Suitable
 Black BL	✓		

Solid colours

	Very Good	Moderate	Not Suitable
 Burgundy BU	✓		
 Denim Blue DE	✓		
 French Navy FRNA	✓		
 Sport Grey SG		✓	
 Light Heather LHE		✓	
 Dark Heather DHE		✓	

Faded colours

	Very Good	Moderate	Not Suitable
 Faded Pink FPK	✓		

Printing Guide

Print type	Print type	Printing suitability 0 = Not Suitable, 1 = Poor, 2 = Moderate, 3 = Good, 4 = Very Good, 5 = Excellent	Printing recommendations
Fleece 100% Organic Cotton solid colours (excluding RFD & Sueded colours)	Screen print	★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Discharge	★★★★★	The results may vary from one colour to another. Refer to our discharge printing recommendations on the following page.
	Transfer (Sticker)	★★★★☆	Follow manufacturer's recommendations for curing settings.
	Direct to garment	★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Embroidery	★★★★★	Direct embroidery, stitched patch, labels

***Maximum heat recommendation for back neck label** Fusing 180°C / 3-6 sec, 6 psi
Curing 180°C / 1 min

Print type	Print type	Printing suitability 0 = Not Suitable, 1 = Poor, 2 = Moderate, 3 = Good, 4 = Very Good, 5 = Excellent	Printing recommendations
Fleece 100% Organic Cotton Sueded Colours	Screen print	★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Discharge	★★★★★	The results may vary from one colour to another. Refer to our discharge printing recommendations on the following page.
	Transfer (Sticker)	★★★★☆	Follow manufacturer's recommendations for curing settings.
	Direct to garment	★★★★☆	Follow manufacturer's recommendations for printing and curing settings.
	Embroidery	★★★★★	Direct embroidery, stitched patch, labels

***Maximum heat recommendation for back neck label** Fusing 180°C / 3-6 sec, 6 psi
Curing 180°C / 1 min